

Product Introduction



CDX-1200



CDX-2400



CDM-3600

CDX-1200 & CDX-2400

Our **CDX Series CD Players** include the **CDX-1200** Professional 2U Single CD Player and the **CDX-2400** Professional 2U Dual CD Player. Both models offer all the functionality of high-end CD players at an affordable price. The instant response buttons and jog wheel provide the DJ with quick play and control of the CD or CD-R. Features include a large blue backlit LCD display (one per side for the **CDX-2400**), seamless loop with re-loop, variable pitch control with a 16% range, single /continuous play modes, anti-shock using RAM buffer memory and many more features you would expect from a high end professional player. The control unit of the **CDX-2400** is separate from the CD unit, allowing for greater placement within your rack for expanded ease of use. The **CDX-1200** and **CDX-2400** CD players are leaders in their class, providing professional quality, with multiple features that can be used for any application.

FEATURES

- Instant-Start & Cue with Preview
 - Variable Pitch Control with a 16% Range
 - Single/Continuous Play Modes
 - Pitch Bend via Jog Wheel or Buttons
- Three Mode Time Selection
 - Frame Accurate Search
 - Audio CD & CD-R Compatible
 - Large Blue Backlit LCD Display
- Seamless Loop with Reloop (Per Side on Dual Players)
 - Rubber Jog Wheels with Finger Grips
- Anti-shock using RAM Buffer Memory
 - Two Selectable Jog Modes Pitch Bend/Search

SPECIFICATIONS

GENERAL:		AUDIO SECTION:	
Disc Type.....	Standard Compact Discs (12cm & 8cm)	Quantization.....	1 Bit Linear/ Channel, 3 Beam Laser
Time Display.....	Track Elapsed, Track Remain, or Total Remain	Oversampling Rate.....	8 Times
Variable Pitch.....	± 16% Slider with Resume Switch	Sampling Frequency.....	44.1 kHz
Pitch Bend.....	± 16% Maximum	Frequency Response.....	20 Hz to 20 kHz
Instant Start.....	Within 0.03 seconds	Total Harmonic Distortion.....	Less Than 0.05%
Installation.....	2U 19"	Signal to Noise Ratio & Dynamic Range.....	85 dB
		Channel Separation.....	85 dB (1 kHz)
		Output Level.....	2.0 +/- 0.2V R.M.S.
		Power Supply.....	AC 115/ 230V, 60/ 50 Hz

CDM-3600

The **CDM-3600** Professional table top dual deck CD player/audio mixer combo is an Integrated DJ System designed for Mobile DJ's, DJ's just starting out or hobbyists. The CD player section offers all the functionality of high-end, professional CD players. The instant response buttons and jog wheels provide for independent quick play and control of two CD's or CD-R's. Features include two (one per side) large blue backlit LCD displays, fully programmable with repeat function, seamless loop with reloop, variable pitch control with a 16% range, single /continuous play modes, anti-shock using RAM buffer memory and many more features you would expect from a high end CD player. The two channel mixer, offers a 3-band EQ with Gain Control, has a ¼" headphone output, balanced XLR outputs, ¼" mic input and auxiliary inputs for phono or line devices plus many more features. Add powered speakers to the **CDM-3600** and your ready to mix like the pros.



FEATURES

- Includes all features above in CDX-2400 and also:*

 - Fader-Start Capability
 - Direct Track Access Buttons
 - Fully Programmable with Repeat Function
- ¼" Headphone Output
 - XLR & ¼" Mic Input
 - Auxiliary Inputs for Phono or Line Devices
- +10 Track Button for Quick Navigation
 - 3-Band EQ with Gain Control

SPECIFICATIONS

<i>Includes all specifications above in CDX-2400 and also:</i>		INPUTS:	OUTPUTS:
		Phono.....	Max.....
		Line.....	Rec.....
		MIC.....	

*Specifications subject to change without notification for improvement

CD Players/ Mixer	CDX-1200	CDX-2400	CDM-3600
Unit Dimensions	19" x 3.5" x 10" (482 x 89 x 255 mm)	19" x 3.5" x 10" (482 x 89 x 255 mm) [Remote: 19" x 3.5" x 2.75" (482 x 133 x 70 mm)]	19" x 10.2" x 4.3" (482 x 260 x 110 mm)
Weight	5.5 lbs (2.5 kgs)	13.7 lbs (6.2 kgs) [Remote: 4 lbs (1.5 kgs)]	12.1 lbs (5.5 kgs)
Shipping	10.7 lbs (4.89 kgs)	21 lbs (9.5 kgs)	15.6 lbs (7.1 kgs)

GCI Technologies Corp.
Gemini Sound Products, S.A.
GCI Technologies Corp. GmbH
GCI Technologies Corp., Ltd.
GCI Technologies Corp., S.A.R.L.

1 Mayfield Avenue, Edison, NJ, USA 08837
Caspé 172 , 1A, 08013 Barcelona, Spain
Lerchenstrasse 14, Haus 3 – 1. Stock, 80995 München, Munich, Germany
Unit 44 Brambles Enterprise Center, Waterberry Drive, Waterlooville, PO7 7TH, UK
Parc de Levenement 1, Allée d'Effiat, 91160 Longjumeau, France

T: +1 732 346 0061
T: +34 93 436 37 00
T: +49 (0) 89 319 019 80
T: +44 (0) 87 087 00880
T: +33 (0) 1 69 79 97 70

Email: sales@gci-technologies.com
Email: info.spain@gci-technologies.com
Email: info.germany@gci-technologies.com
Email: sales.uk@gci-technologies.com
Email: info.france@gci-technologies.com

© GCI Technologies Corp. 2007 All Rights Reserved

Rail Glide™ is a registered trademark of GCI Technologies Corp.

Rev. 09.07